



TUHH

Hamburg University of Technology

Construction of Urine Diverting Dry Toilets

Dipl.-Ing. Stefan Deegener, Research Engineer

Alp Ergünsel, M.Sc., Research Engineer

Univ. Prof. Dr.-Ing. Ralf Otterpohl, Director

Institute of Municipal and Industrial



Institute of Wastewater Management
and Water Protection

TUHH

Technische Universität Hamburg-Harburg

Topics:

- Introduction and Basic Informations
- Urine-Diverting Dry Toilets
- Examples of UD Dry Toilets
- How to use UD Dry Toilets
- How to build UD Dry Toilets
- Summary

Double Vault Urine Diverting Dry Toilet




Institute of Wastewater Management
and Water Protection



Technische Universität Hamburg-Harburg

Scheme of Urine Diverting Toilets




Household UDDT inside the house in Armenia (under construction)



Separation of urine and faeces



- Faeces
- Urine



Dry Toilets with Urine Diversion



Kathmandu, enpho.org

UD-Toilet with children seat



Institute of Wastewater Management
and Water Protection

BB innovation, Sweden



Technische Universität Hamburg-Harburg

UD- Dry Toilets from Philippines



— **aww** —

Institute of Wastewater Management
and Water Protection

TUHH

Technische Universität Hamburg-Harburg



Meilong
Ceramics,
China

Urine Diverting Toilet from Concrete



Китайский сухой туалет



Urine Diverting Toilet from Concrete



aww

Institute of Wastewater Management
and Water Protection

TUHH

Technische Universität Hamburg-Harburg

Waterless Urinals - before



Institute of Wastewater Management
and Water Protection




Technische Universität Hamburg-Harburg

Waterless Urinals - after



Odour trap Urinal



— **aww** —

Institute of Wastewater Management
and Water Protection

TUHH

Technische Universität Hamburg-Harburg

Odour trap Urinal



Two chamber Urine-tank



Urine Storage





Institute of Wastewater Management
and Water Protection

(Høglund 2001)



Technische Universität Hamburg-Harburg



Winter Times



Single Vault vs. Double Vault

Single Vault:

- Container needed for feaces
- Cheaper (smaller)
- Post-composting required
- Seat dont have to be replaced
- Handling with fresh faeces



Single Vault-UDDT in Ukraine



Institute of Wastewater Management
and Water Protection



Technische Universität Hamburg-Harburg

Single Vault vs. Double Vault

Double Vault:

- Drying of the feaces in the toilet
- expensive (bigger area)
- possibly post-composting needed
- Seat has to be replaced

Double Vault in Ukrainian School



Institute of Wastewater Management
and Water Protection




Technische Universität Hamburg-Harburg

UDDT for Romanian Townhall (2006)



Double-vault latrine



Finished Toilethouse in Romanian school



Finished Toilethouse




Institute of Wastewater Management
and Water Protection



Technische Universität Hamburg-Harburg

Inside Toilets



Waterless Urinals in school



Household Toilet in Ukraine




Dry Toilets in Germany



Toilet in Hamburg




Toilet in Hamburg





Espacio de Salud
Cuernavaca, Morelos
MEXICO

Schooltoilet in Poltava (Oct 2004)



Institute of Wastewater Management
and Water Protection



Technische Universität Hamburg-Harburg


Lismore, Australia (near Brisbane)



Gebers, Stockholm, Sweden

Housing project

80 inhabitants



Separation toilet

Only urine is
flushed with 0.1 l
of water



Containers for collection of faecal matter



140 l – bins below toilets collect undiluted faeces with toilet paper



Secondary composting
outside the dwelling together
with biowaste

Composting of Faeces





Composted Faeces




Palsternackan Project - Sweden

Palsternackan Project

- 51 appartements, 160 residents
- Urine separating tanks.
- Polyethylene pipe systems.
- Three urine holding tanks
- Three urine storage tanks.
- Remaining wastewater enters Stockholm wastewater system.




Palsternackan Project - Sweden



Dimensions, inclination of pipes and capacity of holding tanks



Tank trucks transporting urine



Settlement 'Allermöhe', Hamburg, Germany



123 ha

34 housing units


Constructed Wetland for greywater:



<http://www.oeko-siedlung-allermoehe.de/>

- Dry toilets: blackwater and organic waste treated in composter
- Greywater treated in planted soil filter

Settlement 'Allermöhe', Hamburg



Composting chambers in basement

Settlement ‚Allermöhe‘, Hamburg, Germany


Retrofitting Urine-Diversion:



UDDT in multi-story apartments in Dong Sheng, China (SEI)



(EcoSan Res/
A. Rosemarin 2005)




Settlement 'Braamwisch', Hamburg, Germany




- 40 housing units
- Blackwater separate, treatment in composter
- Greywater in planted soil filter
- Solar energy usage

Як правильно користуватися еко-туалетом


Toaleta Ecosan este realizată după un concept inițial al lui Cesar Anorve, Centre of Innovation in Alternative Technology, Mexico
Material educational realizat de Claudia Wendland, Universitatea Tehnică Hamburg, Germania



**Малий отвір
призначено
для сечі,
великий – для
калу.**



**Після завершення
туалету кал
необхідно
присипати
землею / попелом
Тільки не кидайте
землю у отвір для
сечі!!!**




**Сеча не повинна
потрапляти до
відсіку з калом!**

**Користуйтесь
пісуаром!**



**Після
відвідування
туалету добре
мийте руки з
милом!!!**







Sawdust, ashes or
soil
after defaecation

Urine collection

Urine and Faeces mixed



Recycling of Nutrients



Closing the Nutrient-Cycle



Closing the Nutrient-Cycle



Application of urine in agriculture in Sweden



Source: Urine separation-closing the nutrient cycle, final report on the R&D project source separated human urine-a future source of fertilizer for agriculture in the Stockholm region

Enhanced vegetable growth using “pit toilet compost”.



Photos: Peter Morgan

URINE




Photos: Peter Morgan


trials with urine on maize



A major advantage of Ecological Sanitation is the closed food cycle:



Cross-section toilet-house



Institute of Wastewater Management
and Water Protection



Technische Universität Hamburg-Harburg

Earthworks for Foundation



— **aww** —

Institute of Wastewater Management
and Water Protection

TUHH

Technische Universität Hamburg-Harburg

Floor of Faeces-Chambers



Faeces Chambers Walls



Hole for urine-pipes

Frame for superstructure



Building frame and walls



Construction of the Roof



Ventilation of
Faeces
chamber

Urine-piping



Outside View of finished Toilet



Institute of Wastewater Management
and Water Protection




Technische Universität Hamburg-Harburg

Inside View of finished Toilet



Benefits of Urine Diverting Dry Toilets

- ✓ Offer a high level of comfort and hygiene
- ✓ No water pollution
- ✓ No smell
- ✓ Does not attract flies
- ✓ No waste of water and nutrients
- ✓ Produce excellent fertiliser and soil conditioner
- ✓ No water connection needed
- ✓ Can be built inside
- ✓ Save Money



Thank you for your attention!

For further information please
contact:

Alp Ergünsel

Stefan Deegener

phone: +49 - (0) 40 - 42 878 - 2722

e-mail: erguensel@tuhh.de

www.tuhh.de/aww

www.ecosan.org

